



ptimum *new range*



Solar module (60 cells 6")
A-xxxM GS (320/325/330 W)

- **Optimize your instalations.**
- High module **efficiency** and stable power output based on leading process technology.
- **Outstanding electrical performance** under high-temperature conditions or low-irradiance conditions.
- Ease of installations due to the **innovative engineering design.**
- **Rigorous quality control** meets the highest international standard.
- **Warranty, 10-year** workmanship and **25-year** performance (80% power output).





A-xxxM GS (ES) (xxx = rated power)

Electrical characteristics	A-320M GS	A-325M GS	A-330M GS
Maximum Power (Pmax)	320W	325 W	330 W
Maximum Power Voltage (Vmp)	33.40 V	33.60 V	33.80 V
Maximum Power Current (Imp)	9.59 A	9.68 A	9.77 A
Open Current Voltage (Voc)	40.90 V	41.10 V	41.30 V
Short Circuit Current (Isc)	10.15 A	10.20 A	10.31 A
Module Efficiency (%)	19.18	19.48	19.78
Power Tolerance (W)		0/+5	
Maximum Series Fuse Ratings (A)		20	
Maximum System Voltage (TUV)		DC 1000 V	
Normal Operating Cell Temperature (°C)		45±2	

Electrical characteristics tested at Standard Test Conditions (STC), defined as: Irradiance of 1000 w/m², spectrum AM 1.5 and temperature of 25 °C.
 Tolerance measures STC: ±3% (Pmp); ±10% (Isc, Voc, Imp, Vmp).
 Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3%

Mechanical specifications


Dimensions (± 2 mm.)	1665x1002x35 mm
Weight (± 0,5 kg)	19.00 kg
Max. static load, front (snow & wind)	5400 Pa
Max. static load, back (wind)	2400 Pa
Max. hailstone impact (diameter/velocity)	25 mm / 23 m/s

Construction materials

Front cover (material /type/thickness) (*)	Tempered Glass,High Transmission/Low Iron/3.2 mm
Cell (quantity/type/dimensions) (**)	60 cells (6x10)/Mono PERC /158.75 x 158.75 mm
Frame (material/color)	Anodized aluminium alloy /Black
Junction box (protection degree)	IP67
Cable (length/cross-section area)/Connector	1.200 mm / 4 mm ² / Combinable MC4

(*) With anti-reflective coating / (**) Cell color: Black / Backsheet Color: Black

Panel construction generic view



The drawing is not to scale


Temperature characteristics

Temp. Coeff. of Isc (TK Isc)	0.048% /°C
Temp. Coeff. of Voc (TK Voc)	-0.28% /°C
Temp. Coeff. of Pmax (TK Pmax)	-0.37% /°C
Operating Temperature	-40 to +85 °C


Packaging

Modules/pallet	31 pcs
Pallets/container 40' HQ	28 pallets
Modules/container 40' HQ	868 pcs
Pallets/container 20'	12 pallets
Modules/container 20'	372 pcs

Various Temperature (A-325M GS)



Various Irradiance (A-325M GS)



Official distributor:

DPV ENERGY
 Edificio Condes de Buñol
 C/ Isabel la Católica, 8
 46004 Valencia (Spain)
 +34 963 318 066
 info@dpvenergy.com



NB: The data contained in this documentation are subject to modification without prior notification.

➔ www.atersa.com • atersa@elecnor.com
 Madrid (Spain) +34 915 178 452 • Valencia (Spain) +34 961 038 430

Latest revision: **24/04/20**
 Ref.: **EN-MU-6M 6x10 GS MN TN (SS)(1)-A (DPV)-BC**
 © Atersa SL, 2016



IEC 61215
 IEC 61730