



Vertex S*

— i-*TOPCon* *Ultra* —

Shield TSM-NED9R.28 445-470W

Key Features




VKF HW4 Hail Test



Standard load capacity: +7000/-5000 Pa



Fire rating (IEC 61730-2): Class A+A



High customer value

- Suitable for residential and C&I rooftop
- Perfect size for handling and installation
- Compatible with mainstream inverters and diverse mounting systems



High power up to 470W


- Up to 23.5% module efficiency, on 210 innovative platform
- Patented i-*TOPCon* technology with continuous efficiency improvement, including contact resistance reduction, rear recombination enhancement and edge quality repairment



High reliability with double glass

- Less prone to micro-cracks and scratches on the back side
- Excellent fire rating, weather resistance, sustainable in harsh environments and extreme weather conditions
- Up to 25 years product warranty and 30 years power warranty

Performance Warranty



* Please refer to product warranty for details

Comprehensive Products and System Certificates

IEC61215/IEC61730/IEC61701/IEC62716

ISO 9001: Quality Management System

ISO 14001: Environmental Management System

ISO14064: Greenhouse Gases Emissions Verification

ISO45001: Occupational Health and Safety Management System



ELECTRICAL DATA (STC)

Peak Power Watts- $P_{MAX}(W_p)^*$	445	450	455	460	465	470
Power Selection (W)**	0 ~ +5					
Maximum Power Voltage- V_{MPP} (V)	44.30	44.60	45.00	45.40	45.80	46.10
Maximum Power Current- I_{MPP} (A)	10.05	10.09	10.11	10.14	10.16	10.20
Open Circuit Voltage- V_{oc} (V)	52.60	52.90	53.40	53.80	54.20	54.60
Short Circuit Current- I_{sc} (A)	10.71	10.74	10.77	10.81	10.85	10.89
Module Efficiency η_m (%)	22.3	22.5	22.8	23.0	23.3	23.5

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5. *Measuring tolerance: $\pm 3\%$. **Power selection up to: +3%.

ELECTRICAL DATA (NOCT)

Peak Power Watts- $P_{MAX}(W_p)$	341	344	348	352	355	359
Maximum Power Voltage- V_{MPP} (V)	41.70	42.00	42.30	42.70	42.80	43.20
Maximum Power Current- I_{MPP} (A)	8.17	8.19	8.22	8.25	8.28	8.31
Open Circuit Voltage- V_{oc} (V)	49.90	50.20	50.60	51.00	51.40	51.70
Short Circuit Current- I_{sc} (A)	8.63	8.66	8.68	8.71	8.74	8.78

NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature) 43°C ($\pm 2^\circ\text{C}$)

Temperature Coefficient of P_{MAX} - 0.29% /°C

Temperature Coefficient of V_{oc} - 0.24% /°C

Temperature Coefficient of I_{sc} 0.04% /°C

Due to different testing methods, the actual performances might differ from the declared specifications.

APPLICATION CONDITIONS


Operating Temperature -40~+70°C

Maximum System Voltage 1500V DC (IEC)


Max Series Fuse Rating 25A

CURVES OF PV MODULE

I-V CURVES OF PV MODULE (465W)




P-V CURVES OF PV MODULE (465W)



MECHANICAL DATA

Solar Cells	N-type i-TOPCon Monocrystalline
No. of cells	144 cells
Module Dimensions	1762×1134×30 mm (69.37×44.65×1.18 inches)
Weight	27 kg (59.52lb)
Front Glass	AR Coating Heat Strengthened Glass
Back Glass	Heat Strengthened Glass
Frame	30mm(1.18 inches) Anodized Aluminium Alloy, Black
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm ² (0.006 inches ²) Portrait: 200/320 mm(3.78/11.02 inches) Length can be customized
Connector	TS4 Plus / TS4 / MC4 EV02*
Packaging	Modules per box: 36 pieces Modules per 40' container: 900pieces

*The connector names listed are general names; specific types are subject to the certification documents.



www.trinasolar.com

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.
© 2025 Trina Solar Co., Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.
The right of final interpretation belongs to Trina Solar Co., Ltd.
Version number: TSM_EN_2025_A